Microwaves & RF 2002 Editorial Index

COMMERCIAL

▲ Taking on the recession with "breakthrough" products (March, p. 33)

COMMUNICATIONS

▲ Universal modulator spans 2 to 18 GHz (February, p. 136)
▲ Linearity/power considerations in 5-GHz WLANs (March, p. 65)
▲ Synthesizers offer submicrosecond switching (June Cover, p. 98)
▲ Single CMOS chip receives GPS signals (June, p. 108)
▲ Splitters/couplers distribute in-building wireless signals (June, p. 116)
▲ Efficiently modulate UWB signals (September, p. 59)
▲ Weinschel celebrates 50 years of excellence (November, p. 33)

COMPONENTS

▲ TIAs clear way for 40-Gb/s systems (January, p. 33)
▲ Seeking light at the end of the fiber (February, p. 33)
▲ Multichannel IF amplifier bypasses AGC circuitry (February, p. 104)
▲ DDS enhances ovenized oscillator (March Cover, p. 100)
▲ GSM/GPRS/EDGE chips form triband transceiver (March, p. 106)
▲ Handset amplifiers arrive from new source (March, p. 116)
▲ Line of stripline filters offers many benefits (March, p. 126)
▲ Balanced LNA suits cellular base stations (April, p. 70)
▲ Compact components handle high power (May, p. 159)
▲ VCO-core chip solves module size, cost problems (May, p. 168)
▲ Waveguide components form V-band links (May, p. 171)
▲ LCP material now suits high-frequency circuits (May, p. 174)
▲ Setting bias points for linear RF amplifiers (June, p. 71)
▲ Design narrowband filters with open-source software (June, p. 82)
▲ Bluetooth components target embedded solutions (June, p. 118)
▲ Tracking advances in VCO technology (July, p. 53)
▲ Setting bias points for linear RF amplifiers (July, p. 66)
▲ YIGs tune high-speed millimeter-wave radios (July Cover, p. 92)
▲ Printed dipole antenna has integrated balun for 5-GHz WLANs (August, p. 68)
▲ FBAR duplexers screen PCS band (August, p. 116)
▲ Clock translators upgrade data links (September Cover, p. 110)

Microwaves & RF 2002 Editorial Index

COMMERCIAL

▲ Taking on the recession with "breakthrough" products (March, p. 33)

COMMUNICATIONS

▲ Universal modulator spans 2 to 18 GHz (February, p. 136)
▲ Linearity/power considerations in 5-GHz WLANs (March, p. 65)
▲ Synthesizers offer submicrosecond switching (June Cover, p. 98)
▲ Single CMOS chip receives GPS signals (June, p. 108)
▲ Splitters/couplers distribute in-building wireless signals (June, p. 116)
▲ Efficiently modulate UWB signals (September, p. 59)
▲ Weinschel celebrates 50 years of excellence (November, p. 33)

COMPONENTS

▲ TIAs clear way for 40-Gb/s systems (January, p. 33)
▲ Seeking light at the end of the fiber (February, p. 33)
▲ Multichannel IF amplifier bypasses AGC circuitry (February, p. 104)
▲ DDS enhances ovenized oscillator (March Cover, p. 100)
▲ GSM/GPRS/EDGE chips form triband transceiver (March, p. 106)
▲ Handset amplifiers arrive from new source (March, p. 116)
▲ Line of stripline filters offers many benefits (March, p. 126)
▲ Balanced LNA suits cellular base stations (April, p. 70)
▲ Compact components handle high power (May, p. 159)
▲ VCO-core chip solves module size, cost problems (May, p. 168)
▲ Waveguide components form V-band links (May, p. 171)
▲ LCP material now suits high-frequency circuits (May, p. 174)
▲ Setting bias points for linear RF amplifiers (June, p. 71)
▲ Design narrowband filters with open-source software (June, p. 82)
▲ Bluetooth components target embedded solutions (June, p. 118)
▲ Tracking advances in VCO technology (July, p. 53)
▲ Setting bias points for linear RF amplifiers (July, p. 66)
▲ YIGs tune high-speed millimeter-wave radios (July Cover, p. 92)
▲ Printed dipole antenna has integrated balun for 5-GHz WLANs (August, p. 68)
▲ FBAR duplexers screen PCS band (August, p. 116)
▲ Clock translators upgrade data links (September Cover, p. 110)

Microwaves & RF 2002 Editorial Index

▲ Quad-band PA module powers GSM and GPRS (September, p. 118)
▲ Push-on connectors make links to 65 GHz (October, p. 110)
▲ Selecting crystals for stable oscillators (November, p. 53)
▲ Flexible printed antennas span 100 kHz to 40 GHz (November, p. 64)
▲ DACs deliver multiple carriers (November Cover, p. 95)
▲ Broadband amplifiers drive OC-768 modulators (November, p. 104)
▲ Oscillators: A new look at an old model (December, p. 51)
▲ Designing antennas for indoor millimeter-wave use (December, p. 61)
▲ Build LNAs with an integrated approach (December, p. 79)
▲ Integrated power amp covers GSM/DCS/PCS (December, p. 112)
▲ Diversity antenna module broadens wireless range (December, p. 114)

COMPUTER-AIDED ENGINEERING

▲ Software helps visualize system performance (January, p. 102)
▲ Simulate an I/Q modulator (February, p. 86)
▲ Microwave software eases PA combiner/divider design (February, p. 93)
▲ Software suite simplifies simulations (February, p. 122)
▲ Software speeds cell-site surveys (February, p. 134)
▲ EM simulator gets boost with 64-b code (March, p. 122)
▲ Improve BPF performance with wiggly coupled lines (April, p. 53)
▲ Scanning technique sorts skin permittivity (May, p. 106)
▲ Open architecture solves large 3D puzzles (May Cover, p. 144)
▲ Waveform analysis is forte of digital storage scope (May, p. 166)
▲ Vector modulators deliver fast phase/amplitude changes (May, p. 176)
▲ Software-defined receiver captures 20 to 2700 MHz (June, p. 104)
▲ Software selects optimum solver (June, p. 110)
▲ Avoid frequency extrapolation errors (September, p. 98)
▲ Design/verification tools tame complex system designs (October, p. 84)
▲ Modeling 802.11a-based WLAN systems (November, p. 87)

CONFERENCES

▲ Innovations flourish at Wireless Systems 2002 (April, p. 33)
▲ Seattle is home to 50th MTT-S show (May, p. 33)
▲ Attendance grows at RF & Hyper Europe (June, p. 33)
▲ Conference tackles 3G test challenges (June, p. 39)
▲ MEMS devices emerge at 2002 Seattle MTT-S (August, p. 33)
▲ Conference targets military electronics (September, p. 33)
▲ 2002 IEDM explores emerging semiconductors (October, p. 33)
▲ Reference designs liven wireless show (December, p. 36)

CROSSTALK

▲ Mike Snyder, President of KDI (May, p. 63)

Our Website has full details on over 2000 components

www.dorado-intl.com

- ANTENNAS (1-110 GHz) *Horns and Planar Arrays*
- ISOLATORS & CIRCULATORS (0.1-110 GHz) *Coax, Drop-in/Microstrip, Waveguide*
- WAVEGUIDE PARTS (8.2-110 GHz) *Adapters, Attenuators, Bends, Couplers, Loads, Phase Shifters, Shorts, Straights, Switches, Tuners, Tees, Transitions, Twists*

DORADO INTERNATIONAL | 716 Industry Dr., Seattle, WA 98188 | telephone (206) 574.0900 | fax (206) 574.0912 | e-mail doradoint@aol.com

● Enter NO. 432 at www.mwrf.com

Microwaves & RF 2002 Editorial Index

DEVICES & ICs

▲ Biasing high-power GaAs FET devices (January, p. 66)
▲ Miniature PLL module locks 1500 to 1600 MHz (February, p. 132)
▲ Setting bias in high-power GaAs FET devices (March, p. 80)
▲ MMIC amps add gain and isolation (April Cover, p. 86)
▲ Base-station antennas offer dual polarization (May, p. 99)
▲ TD-SCDMA Txs hone base-station efficiency (May, p. 117)
▲ Dual-band cellular PA strives for efficiency (May, p. 129)
▲ Demodulator extends range of telemetry systems (May, p. 156)
▲ Increase MMIC yield with statistical design (June, p. 59)
▲ Active SiGe mixers transmit 800 to 2500 MHz (June, p. 121)
▲ ICs send 100 Mb/s using UWB technology (July, p. 98)
▲ Chip set offers compact 2.4-GHz WLAN solution (August Cover, p. 102)
▲ Novel mHEMTs signal transistor evolution (August, p. 57)
▲ Method boosts bandwidth of IFAs for 5-GHz WLAN NICs (September, p. 66)
▲ ASIC stabilizes crystal oscillators (September, p. 124)
▲ Single chip realizes direct-conversion Rx (October, p. 55)
▲ Low-power transceiver targets wireless headsets (October, p. 68)
▲ GPS receiver IC offers embedded solution (October, p. 108)
▲ Buffer amplifiers solve VCO problems (November, p. 82)
▲ Real-time processing merges with low power efficiency (November, p. 106)
▲ RF ICs complement full device portfolio (November, p. 108)
▲ 400-Msamples DDSs run on only +1.8 VDC (December Cover, p. 101)

MATERIALS

▲ Design NMR probes at high frequencies (February, p. 77)
▲ Design an analog GSM handset power-control loop (April, p. 64)
▲ Conductive silicones supply flexible shielding (September, p. 120)

PDD

Your Online Resource

For RF and Microwave Products and Manufacturers

Electronic engineers typically create designs that require hundreds and, sometimes, thousands of different components from a wide range of suppliers. Finding the optimum components for a design from a reliable vendor can be an exercise in futility without the proper research tools. And one of the most important reference sources is the online version of the Microwaves & RF Product Data Directory at www.m-rf.com.

This powerful website and search engine offers thousands of high-frequency manufacturers, searchable by means of more than 500 different product categories, from amplifiers to wire. The site provides access to names, addresses, telephone numbers, FAX numbers, e-mail addresses, and even provides active links to key suppliers.

Take a few minutes to set up your user file at www.m-rf.com. After that, you'll be able to log on in second by just entering your telephone number. While you're on the site, don't forget to check out the more than 500 New Product listings, with key specifications for everything from systems to semiconductors.

If you need a part, you'll find it at:

www.m-rf.com

Microwaves & RF 2002 Editorial Index

SYSTEMS & SUBSYSTEMS

- ▲ Constructing circuits for short-range radios (February, p. 59)
- ▲ System automates accelerated life tests (February, p. 128)
- ▲ Tracking phase noise in short-range radios (March, p. 57)
- ▲ WDM couplers cut optical losses (May, p. 162)
- ▲ Digitizer family characterizes high-speed signals (May, p. 164)
- ▲ Introducing loop antennas for short-range radios (July, p. 80)
- ▲ Matching loop antennas to short-range radios (August, p. 72)
- ▲ Modular synthesizers shave phase noise (August, p. 110)
- ▲ Gauge nonthermal effects of microwave fields (September, p. 72)

TEST & MEASUREMENT

- ▲ Understand Bluetooth protocol testing (January, p. 57)
- ▲ Gauge phase jitter and noise in VCXOs (January, p. 78)
- ▲ Digital generator makes programmable noise (January Cover, p. 96)
- ▲ System simulator melds DSP and RF analysis (February Cover, p. 116)
- ▲ Specify jitter and phase noise in VCXOs (March, p. 76)
- ▲ Integrated VGA aids precise gain control (March, p. 88)
- ▲ CRU recovers 40-Gb/s OC-768 clock signals (April, p. 94)
- ▲ Adapter converts scope to 1-GHz spectrum analyzer (April, p. 100)
- ▲ EM approach sets new speed records (May, p. 81)
- ▲ DDS module shaves spurious noise (May, p. 180)
- ▲ Generators deliver vector modulation (July, p. 33)
- ▲ VNA series gains range and features (July, p. 95)
- ▲ New methods debug wireless protocols (August, p. 88)
- ▲ Impedance tuners aid PA efficiency (September, p. 86)
- ▲ Signal source carries vector modulation to 20 GHz (September, p. 116)
- ▲ Network analyzers simplify mixer test (October Cover, p. 98)
- ▲ PC card contains Bluetooth protocol analyzer (October, p. 107)
- ▲ Digital RF signal generator breaks down complex tests (October, p. 112)
- ▲ Make precise base-station measurements (November, p. 72)
- ▲ Oscilloscope conquers speed and high bandwidth (November, p. 102)
- ▲ SUSS's brand of Vermont technology (December, p. 33)
- ▲ Modulated S-parameters tackle wideband devices (December, p. 90)